

## Product Specification Sheet

### ERT-PP / EF-PP / JER-PP

Printable with wax ribbon (FTA-LW...x...) for paper labels

#### Permanent, matte white paper labels on roll for thermal transfer printers

##### Material Thickness:

	Value (Tolerance)	Unit	Test Method
Facestock	71 (+/- 10%)	micron	ISO 534-80
Adhesive	no information given by manufacturer	micron	
Liner (glassine)	51 (+/- 10%)	micron	ISO 534

##### Adhesive (acrylic in water emulsion):

	Value	Unit	Test Method
Shear Strength	*		
Tack	>11	(N) glass	FTM 9
Cohesion (h)	>2	1 kg	FTM 8
Application Temperature	min. +5	°C	
Temperature Range (Adhesive)	-20 to +80	°C	

\*no information provided by the manufacturer

**Certifications:** Item is REACH and RoHS (2011/65/EU) compliant. Adhesive is approved by ISEGA (Direct contact dry & moist, non fatty foodstuffs) Adhesive complies with EN 71/3 (application on toys); Paper from sustainable forestry (FSC certified).

**Printability:** Suited for thermal transfer printing with wax ribbons (i.e. Armor AWR®8, AWR®470, AWX®FH; Labelident Eco wax; Zebra 2100, 2300) or combination ribbons (i.e. Armor APR®6, APX®FH; Kurz K200, K305; Zebra 3200, 3400).

**Storage:** Material is stable for two years stored at max. 21°C and 50% rel. humidity. Damp conditions, excessive heat and/or cold conditions should be avoided.

**Further Information:** Acrylic permanent adhesive. Good adhesion on a wide variety of materials including apolar substrates (such as PE and PP).

Note: All values are guidelines and not intended for use in setting specifications. The information provided does not constitute any warranty, express or implied, and is intended solely for the recipient and shall not be forwarded to any third party. The buyer of our products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application. Samples of our materials can be provided upon request. Information is subject to change without prior notification. Last Updated: January 2019.