

Product Specification Sheet

EL_._ EB_._ PPRD / EB_._ PPRD500 EL_._ PPBE / EB_._ PPBE / EB_._ PPBE500

**Permanent, matte colored paper labels
 on sheet for full-color copying machines and laser printers**

Material Thickness:

	Value (Tolerance)	Unit	Test Method
Facestock	82 (75-90)	micron	ISO 534
Adhesive	15	micron	
Liner (glassine)	52 (50-58)	micron	ISO 534
<u>Paper grammage:</u>	80	g/m ²	ISO 536

Adhesive (acrylic):

		Value	Unit	Test Method
Shear Strength		100	min	FTM 8
Initial Tack		10,3	N	FTM 9
Peel Resistance	Stainless Steel	15,4	N/25 mm	FTM 1 (72 hours)
	Glass	*		
	Polypropylene	*		
	Paint (automotive)	*		
	PBT	*		
Application Temperature		min. +5	°C	
Temperature Range (Adhesive)		-20 to +80	°C	

*no information provided by the manufacturer

Certifications: Facestock: Packaging and packaging waste Directive 94/62/CE, Electric and electronic equipment (RoHS) Directive 2011/65/EU; Adhesive: Packaging and packaging waste Directive 94/62/CE, EN 71-3 Toy Safety, EN 71-9 Toy Safety, Direct contact with foodsuffs (ISEGA); Liner: Contact with foodstuff (BfR XXXVI), Packaging and packaging waste Directive 94/62/CE, EN 71-3 Toy Safety, Electric and electronic equipment (RoHS) Directive 2011/65/EU.

Printability: Suited for full-color copying machines and laser printers.

Storage: Material is stable for two years stored at max. 21°C and 50% rel. humidity. Damp conditions, excessive heat and/or cold conditions should be avoided.

Further Information: n/a

Note: All values are guidelines and not intended for use in setting specifications. The information provided does not constitute any warranty, express or implied, and is intended solely for the recipient and shall not be forwarded to any third party. The buyer of our products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application. Samples of our materials can be provided upon request. Information is subject to change without prior notification. Last Updated: April 2019.