

Product Specification Sheet

ERT-PA

Printable with wax ribbon (FTA-LW...x...) for paper labels

Removable, matte white paper labels
 on roll for thermal transfer printers

Material Thickness:

	Value (Tolerance)	Unit	Test Method
Facestock	72	micron	
Adhesive	25	micron	
Liner (glassine)	54	micron	
<u>Paper grammage:</u>	70	g/m ²	ISO 536

Adhesive (acrylic):

		Value	Unit	Test Method
Shear Strength		30	min	
Initial Tack		300,0	g/25 mm	
Peel Resistance	Stainless Steel	*		
	Glass	*		
	Polypropylene	*		
	Paint (automotive)	*		
	PBT	*		
Application Temperature		min. +5	°C	
Temperature Range (Adhesive)		-10 to +80	°C	

*no information provided by the manufacturer

Certifications: The material is REACH and RoHS compliant; Paper from sustainable forestry (FSC certified). No animal contents, free of chlorines.

Printability: Suited for thermal transfer printing with wax ribbons (i.e. Armor AWR®8, AWR®470, AWX®FH; Labelident Eco wax; Zebra 2100, 2300) or combination ribbons (i.e. Armor APR®6, APX®FH; Kurz K200, K305; Zebra 3200, 3400).

Storage: Material is stable for two years stored at max. 21°C and 50% rel. humidity. Damp conditions, excessive heat and/or cold conditions should be avoided.

Further Information: Degree of removability depends on surface and method of application (testing recommended prior to use). Backing paper designed for automatic label generation. Ideal for photocells dispensing system.

Note: All values are guidelines and not intended for use in setting specifications. The information provided does not constitute any warranty, express or implied, and is intended solely for the recipient and shall not be forwarded to any third party. The buyer of our products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application. Samples of our materials can be provided upon request. Information is subject to change without prior notification. Last Updated: April 2019.