

Product Specification Sheet

ERT-PPOP

Printable with wax ribbon (FTA-LW...x...) for paper labels

**Permanent, matte white opaque writing paper (satined) labels
on roll for thermal transfer printers**

Material Thickness:

	Value (Tolerance)	Unit	Test Method
Facestock	71 (+/- 3)	micron	DIN EN 20534
Adhesive	18	micron	
Liner (glassine)	55	micron	
<u>Paper grammage:</u>	74	g/m ²	ISO 536

Adhesive (acrylic):

		Value	Unit	Test Method
Shear Strength		*		
Initial Tack		*		
Peel Resistance	Stainless Steel	*		
	Glass	*		
	Polypropylene	*		
	Paint (automotive)	*		
	PBT	*		
Application Temperature		min. +5	°C	
Temperature Range (Adhesive)		-20 to +80	°C	

*no information provided by the manufacturer

Certifications: Material meets REACH and RoHS requirements (2011/65/EU).

Printability: Suited for thermal transfer printing with wax ribbons (i.e. Armor AWR®8, AWR®470, AWX®FH; Labelident Eco wax; Zebra 2100, 2300) or combination ribbons (i.e. Armor APR®6, APX®FH; Kurz K200, K305; Zebra 3200, 3400).

Storage: Material is stable for two years stored at max. 21°C and 50% rel. humidity. Damp conditions, excessive heat and/or cold conditions should be avoided.

Further Information: n/a

Note: All values are guidelines and not intended for use in setting specifications. The information provided does not constitute any warranty, express or implied, and is intended solely for the recipient and shall not be forwarded to any third party. The buyer of our products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application. Samples of our materials can be provided upon request. Information is subject to change without prior notification. Last Updated: April 2019.