

Product Specification Sheet

Telefon: +49 (0) 9721 79398-0
 Telefax: +49 (0) 9721 79398-14
 E-Mail: info@labelident.de
 Internet: www.labelident.com

ERT-RP

Printable with wax ribbon (FTA-LW...x...) for paper labels

Permanent, glossy white paper labels with specialty adhesive
 on roll for thermal transfer printers

Material Thickness:

	Value (Tolerance)	Unit	Test Method
Facestock	71	micron	
Adhesive	45	micron	
Liner (glassine)	63	micron	
<u>Paper grammage:</u>	80	g/m ²	ISO 536

Adhesive (acrylic):

	Value	Unit	Test Method
Shear Strength	Very high		
Initial Tack	Very high	N	
Peel Resistance	Stainless Steel	Very high	
	Glass	*	
	Polypropylene	*	
Application Temperature	min. -10	°C	
Temperature Range (Adhesive)	-40 to +60	°C	

*no information provided by the manufacturer

Certifications: Material meets REACH and RoHS requirements. Solvent, halogens and silicone, MOSH and MOAH free. Adhesive compliant to FDA 175.105. Compliant to California Proposition 65 and free of POP's (persistent organic pollutants)

Printability: : Suited for thermal transfer printing with wax ribbons (i.e. Armor AWR®8, AWR®470, AWX®FH; Labelident Eco wax; Zebra 2100, 2300) or combination ribbons (i.e. Armor APR®6, APX®FH; Kurz K200, K305; Zebra 3200, 3400).

Storage: Material is stable for one year, stored at max. 25°C and 40-50% rel. humidity. Damp conditions, excessive heat and/or cold conditions, as well as direct sun-light should be avoided.

Further Information: Thick adhesive coat provides for good anchorage on tires, smooth rubber materials, aluminum checker plate, concrete, highly condensed carton and pressed paper materials, dry and smooth as well as saw rough cut wood, wooden and plastic pallets, cast metal parts, PO materials, nonpolar foam materials (open pore such as sponges as well as closed pore such as PP molded parts), polar foam materials made of polyurethane (such as car seats, rubber shoe soles, polystyrene, carpet backing (without small radii) and fruits such as melons.

Product Specification Sheet

Note: All values are guidelines and not intended for use in setting specifications. The information provided does not constitute any warranty, express or implied, and is intended solely for the recipient and shall not be forwarded to any third party. The buyer of our products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application. Samples of our materials can be provided upon request. Information is subject to change without prior notification. Last Updated: April 2019.

Labelident GmbH
 Parisstraße 5
 D-97424 Schweinfurt

Commerzbank Schweinfurt
 SWIFT-BIC: COBADEFFXXX
 IBAN: DE76 7934 0054 0655 2228 00

Amtsgericht Schweinfurt: HRB 4597
 Geschäftsführung: Thomas Simon, Frithjof von Kessel
 Steuernummer: 13/203/03339
 Ust.-ID: DE814048229