

Product Specification Sheet

ERT- VT / EF-VCR

**Permanent, highly clear transparent vinyl labels
on roll for thermal transfer printers**

Telefon: +49 (0)9721 47699-0

Telefax: +49 (0)9721 47699-14

E-Mail: info@labelident.de
Internet: www.labelident.com

Material Thickness:

	Value (Tolerance)	Unit	Test Method
Facestock	50	micron	
Adhesive	no information given by manufacturer	micron	
Liner (glassine)	55	micron	

Adhesive (acrylic):

	Value	Unit	Test Method
Shear Strength	*		
Initial Tack	6,0	N/25 mm	FTM 9
Peel Resistance	Stainless Steel	*	
	Glass	*	
	Polypropylene	*	
	Paint (automotive)	*	
	PBT	*	
Application Temperature	min. +10	°C	
Temperature Range (Adhesive)	-30 to +120	°C	

*no information provided by the manufacturer

Certifications: Material meets REACH and RoHS requirements (2011/65/EU). Adhesive is approved for indirect contact with foodstuffs and direct contact (dry & moist, non fatty foodstuffs). IMDS data available

Printability: Suited for thermal transfer printing with standard resin ribbons (i.e. Armor AXR® 7+, Kurz K504, Zebra 4800, Coding TTR).

Storage: Material is stable for two years stored at max. 21°C and 50% rel. humidity. Damp conditions, excessive heat and/or cold conditions should be avoided.

Further Information: Permanent adhesive with very good adhesion on glass and on a wide variety of substrates, except for apolar (PE, PP).

Note: All values are guidelines and not intended for use in setting specifications. The information provided does not constitute any warranty, express or implied, and is intended solely for the recipient and shall not be forwarded to any third party. The buyer of our products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application. Samples of our materials can be provided upon request. Information is subject to change without prior notification. Last Updated: March 2016.