

## Product Specification Sheet

ERT-PPGG / ERT-PPSG

Telefon: +49 (0)9721 47699-0  
Telefax: +49 (0)9721 47699-14

E-Mail: info@labelident.de  
Internet: www.labelident.com

### Permanent, glossy metallic colored paper labels on roll for thermal transfer printers

#### Material Thickness:

	Value (Tolerance)	Unit	Test Method
Facestock	73 (+/- 5)	micron	ISO 534
Adhesive	25	micron	
Liner (glassine)	55	micron	

#### Adhesive (acrylic):

	Value	Unit	Test Method
Shear Strength	*		
Initial Tack	*		
Peel Resistance	Stainless Steel	*	
	Glass	*	
	Polypropylene	*	
	Paint (automotive)	*	
	PBT	*	
Application Temperature	min. +5	°C	
Temperature Range (Adhesive)	-40 to +100	°C	

\*no information provided by the manufacturer

**Certifications:** Material meets REACH and RoHS requirements (2011/65/EU). Adhesive is approved by ISEGA (Direct contact dry & moist, non fatty foodstuffs) according to the German Recommendations XIV and complies with FDA 175.105. IMDS data available.

**Printability:** Suited for thermal transfer printing with standard or enhanced wax ribbons (i.e. Armor AWR®470, AWX®FH; Zebra 2100), combination ribbons (i.e. Armor APR®6, APX®FH; Kurz K200, K305; Zebra 3200, 3400), or standard resin ribbons (i.e. Armor AXR®7+, Kurz K504, Zebra 4800, Coding TTR).

**Storage:** Material is stable for two years stored at max. 21°C and 50% rel. humidity. Damp conditions, excessive heat and/or cold conditions should be avoided.

**Further Information:** n/a

Note: All values are guidelines and not intended for use in setting specifications. The information provided does not constitute any warranty, express or implied, and is intended solely for the recipient and shall not be forwarded to any third party. The buyer of our products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application. Samples of our materials can be provided upon request. Information is subject to change without prior notification. Last Updated: March 2016.