

Product Specification Sheet

GLT- /KLT- /WA-...x...

**Non-adhesive, coated, white paper labels on roll/on sheet
for thermal transfer printers, full-color copying machines and laser printers**

Technical data:

	Value (Tolerance)	Unit	Test Method
Surface related mass:	170 +/- 10%	g	ISO 536
Thickness	145 +/- 10%	µm	ISO 534
Opacity	About 97%		ISO 2471
Tensile strength lengthwise	110 +/- 10%	N/15 mm	DIN 53112
Tensile strength cross	40 +/- 10%	N/15 mm	DIN 53112

Certifications: Material is REACH and Rohs 2015/863/EU compliant. Meets requirements of regulation (EG) No. 1935/2004, as well as §§ 30 and 31 LFGB and recommendation XXXVI when material is only in contact with dry, not fatty foodstuff.

Printability: Suited for thermal transfer printing, (wax-resin) full-color copying machines and laser printers.

Storage: Material is stable for two years stored at max. 21°C and 50% rel. humidity. Damp conditions, excessive heat and/or cold conditions should be avoided.

Further Information: n/a

Note: All values are guidelines and not intended for use in setting specifications. The information provided does not constitute any warranty, express or implied, and is intended solely for the recipient and shall not be forwarded to any third party. The buyer of our products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application. Samples of our materials can be provided upon request. Information is subject to change without prior notification. Last Updated: February 2021.